(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2



SDS No: Print date: Revision date:

SDS075 04/03/2014 04/07/2013 Page 1 de 13

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. PRODUCT IDENTIFIER

Product Name: Pansement spray (URGO /CARREFOUR)

Type of product: Mixture.

Spray, pressurized liquefied gas.

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Identified uses: Consumer use.

Medical device for general public, dressing.

1.3. DETAILS OF THE SUPPLIER OF THE SUBSTANCE OR MIXTURE

Manufacturer /Supplier: LABORATOIRES URGO

Address: 42 rue de Longvic

21300 Chenôve

Tel: +33.(0)3.80.54.50.00 *Fax:* +33.(0)3.80.44.74.52

Website: www.urgo.fr

Mail c.poste-de-garde@urgo.fr

Contact : Gilles Guérin

1.4. EMERGENCY TELEPHONE

Emergency phone number: INRS / ORFILA: +33.(0)1.45.42.59.59

SECTION 2 HAZARDS IDENTIFICATION

2.1. CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

Classification according to Directive No.1999/45/EC (DDP):

F+; R12 Xi; R36 R66 R67

Full text of hazard categories and R phrases is included in section 16.

Classification according to Regulation EC No.1272/2008 (CLP):

Flam Aerosol Cat 1; H222 Eye Irrit Cat 2; H319 SOT SE Cat 3; H336

EUH066

Full text of hazard categories and H phrases is included in section 16. Procedure used for determining classification is included in section 16.

2.2. LABEL ELEMENTS

Labeling according to Directive No. 1999/45/EC (DDP):

Symbols:



(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2



 SDS No:
 SDS075

 Print date:
 04/03/2014

 Revision date:
 04/07/2013

 Page 2 de 13

F+: Extremely flammable.

Xi: Irritant.

Contains: Ethyl acetate, Nitrocellulose moistened with 30% of isopropanol.

R Phrases:

R12: Extremely flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

S Phrases: S2: Keep out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe spray.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S64: If swallowed, rinse mouth with water (only if the person is conscious).

Reduced labeling (≤ 125 mL):

Symbols: --

Contains:Ethyl acetate, Nitrocellulose moistened with 30% of isopropanol.R Phrases:R66: Repeated exposure may cause skin dryness or cracking.

S *Phrases:* S2: Keep out of the reach of children.

Labeling according to Regulation EC No.1272/2008 (CLP):

Pictograms:





SGH02: Flame.

SGH07: Exclamation mark.

Signal word: Danger.

Contains: Ethyl acetate, Nitrocellulose moistened with 30% of isopropanol.

Hazard statements: H222: Extremely flammable aerosol. H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

EUH066: Repeated exposure may cause skin dryness or cracking.

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P211: Do not spray on an open flame or other ignition source. P251: Pressurized container: Do not pierce or burn, even after use.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray. P271: Use only outdoors or in a well-ventilated area.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P501: Dispose of contents/container appropriately as chemicals, incineration disposal.

Reduced labeling (≤ 125 mL):

Pictograms: --

Signal word: Danger.

Contains: Ethyl acetate, Nitrocellulose moistened with 30% of isopropanol.

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

Precautionary statements: P102: Keep out of reach of children.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P501: Dispose of contents/container appropriately as chemicals, incineration disposal.

Page 3 de 13

SAFETY DATA SHEET

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2

 SDS No:
 SDS075

 Print date:
 04/03/2014

 Revision date:
 04/07/2013

2.3. OTHER HAZARDS

The product has not been evaluated for its properties PBT/vPvB (Regulation EC No. 1907/2006 – Annex XIII).

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1. SUBSTANCES

Not concerned.

3.2. MIXTURES

Constituents / impurities contributing to hazards:

Components	Identifiers	% by mass	Classification (Dir. No.67/548/EEC)	Classification (Regul. EC No.1272/2008)
Ethyl acetate	CAS No: 141-78-6 EC No: 205-500-4 ID No: 607-022-00-5 REACH No: 01-2119475103-46	> 50.0	F; R11 Xi; R36 R66 R67	Flam Liq Cat2; H225 Eye Irrit Cat2; H319 STOT SE Cat3; H336 EUH066
Nitrocellulose moistened with 30% of isopropanol	Nitrocellulose: CAS No: 9004-70-0 EC No: ID No: REACH No: Isopropanol: CAS No: 67-63-0 EC No: 200-661-7 ID No: 603-117-00-0 REACH No:	< 5.0	F; R11 Xi; R36 R67	Flam Liq Cat2; H225 Eye Irrit Cat2; H319 STOT SE Cat3; H336

Full text of hazard categories and R and H phrases is included in section 16.

Constituents / impurities presenting a hazard:

Not concerned.

Constituents / impurities having professional TLV / TWA:

Components	Identifiers	% by mass	Classification (Dir. No.67/548/EEC)	Classification (Regul. EC No.1272/2008)
Ethanol	CAS No: 64-17-5 EC No: 200-578-6 ID No: 603-002-00-5 REACH No: 01-2119457610-43-XXXX	> 25.0	F; R11	Flam Liq Cat2; H225
Dimethyl oxide	CAS No: 115-10-6 EC No: 204-065-8 ID No: 603-019-00-8 REACH No:	qsp	F+; R12	Press Gas Flam Gas Cat1; H220 (*)

Full text of hazard categories and R and H phrases is included in section 16.

SECTION 4 FIRST AID MEASURES

4.1. DESCRIPTION OF FIRST AID MEASURES

Inhalation: Remove victim immediately from source of exposure.

Provide fresh air, if necessary give artificial respiration.

Seek medical advice if symptoms persist.

Seek medical advice if symptoms caused by repeated exposure persist.

Eye Contact: Rinse immediately with plenty of water for 15 minutes.

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2



 SDS No:
 SDS075

 Print date:
 04/03/2014

 Revision date:
 04/07/2013

 Page 4 de 13

Remove contact lenses and open wide the eye.

Seek medical advice immediately.

Immediately rinse mouth and drink plenty of water.

Do not induce vomiting.

Provide rest, warmth and fresh air. Seek medical advice if symptoms persist.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Inhalation: Central nervous system depression including narcotic effects types drowsiness, narcosis,

loss of vivacity altered reflexes, lack of coordination and dizziness.

May irritate the respiratory system.

Skin Contact: Prolonged contact may cause redness, irritation and skin dryness.

Eye Contact: May cause temporary eye irritation.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

No specific recommendations, but first aid may be required in case of accidental exposure by inhalation or ingestion. In case of doubt, CONSULT A DOCTOR!

SECTION 5 FIREFIGHTING MEASURES

5.1. EXTINGUISHING MEDIA

Suitable extinguishing media: In case of fire, use alcohol resistant foam, carbon dioxide, dry powder or water spray.

Adapt fire extinguishing measures to the environment.

Unsuitable extinguishing media: Water jet at high flow.

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

The fumes emitted by thermal decomposition may be toxic: carbon monoxide.

Vapours may form an explosive mixture with air.

Vapours may create a flashover with an ignition source.

Runoff water to sewers may cause fire or explosion.

5.3. ADVICE FOR FIREFIGHTERS

Flammable class: Flammable aerosol Category 1.

Protection against fire: Wear self-contained breathing apparatus and full protective clothing. **Special procedures:** Do not allow firefighting water entering into drains or water courses.

Fire residues and contaminated firefighting water must be disposed of in accordance with

local regulations.

Surrounding fires: Data not available.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Precaution for persons: Respect precautionary statements described in this material safety data sheet.

Take precautionary measures against electrostatic charges. Avoid inhalation of spray mist and contact with skin and eyes.

Keep away from sources of ignition. Ensure adequate ventilation.

Wear safety equipment, keep away unprotected persons.

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2

<u>URGO</u>

 SDS No:
 SDS075

 Print date:
 04/03/2014

 Revision date:
 04/07/2013

 Page 5 de 13

6.2. ENVIRONMENTAL PRECAUTIONS

Precautions for the environment: Collect and dispose waste appropriately.

Do not discharge into drains or the environment.

In case of seepage into water course or sewage, inform appropriate authorities.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Clean up methods: DO NOT TOUCH or walk through spilled material.

Attention, presence of liquefied gas.

Absorb with inert, damp, non-combustible material, and then rinse area with water. Collect spilled material in an appropriate and clean container, seal and dispose of it

according to local regulations.

6.4. REFERENCE TO OTHER SECTIONS

Refer to sections 8 and 13 for more information.

SECTION 7 HANDLING AND STORAGE

7.1. PRECAUTIONS FOR SAFE HANDLING

Handling: Avoid contact with eyes.

Avoid unnecessary exposure.

Keep away from all ignition sources (heat, sparks or open flames).

Ensure adequate ventilation.

Do not pierce container, even after use.

Do not smoke.

Wash hands and other exposed areas with soap and water before eating, drinking,

smoking and when leaving work.

Forming Forklift drivers in the use of fire extinguishers for immediate action.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Store in a cool, dry, well-ventilated area away from direct solar radiation and sources of

ignition.

Keep container tightly closed.

Ensure retention for potential fire extinguishing water. Store in accordance with the rules of incompatibility:
- Criteria for Storage: liquefied flammable gas.

- Incompatible materials: Strong oxidizing agents, oxidizers.

7.3. SPECIFIC END USE(S)

The identified uses for this product are listed in Section 1.2.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. CONTROL PARAMETERS

Worker exposure:

Component Name	CAS No	TLV / TWA	DNEL / DMEL
Ethyle acetate	141-78-6	TWA - 8 h: 400 ppm TWA - 8 h: 1 400 mg/m ³	Industry: Inhalation (short term): 1 468 mg/m³ Inhalation (long term): 734 mg/m³ Dermal (long term): 63 mg/kg/ day
			Consumer: Inhalation (short term): 734 mg/m³

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2



 SDS No:
 SDS075

 Print date:
 04/03/2014

 Revision date:
 04/07/2013

 Page 6 de 13

Component Name	CAS No	TLV / TWA	DNEL / DMEL
			Inhalation (long term): 367 mg/m³ Dermal (long term): 37 mg/kg/day
Ethanol	64-17-5	TLV: 5 000 ppm TLV: 9 500 mg/m ³ TWA: 1 000 ppm TWA: 1 900 mg/m ³	Inhalation (short term / local): 19 mg/m³ Inhalation (long term / systemic): 950 mg/m³ Dermal (long term / systemic): 343 mg/kg/day
Isopropanol	67-63-0	TLV: 440 ppm TLV: 980 mg/m ³	-
Dimethyl oxide	115-10-6	TWA: 1 000 ppm TWA: 1 920 mg/m ³	-

Source: Supplier data; INRS, 2012

Environmental exposure:

Component Name	CAS No	PNEC
Ethyle acetate	141-78-6	Fresh water: 0.26 mg/L Soil: 0.22 mg/kg Sediment: 0.34 mg/kg ITER: 650 mg/L
Ethanol	64-17-5	Fresh water: 0.96 mg/L Seawater: 0.79 mg/L Fresh water sediment: 3.6 mg/kg dw Sediment seawater: 2.9 mg/kg dw Soil: 0.63 mg/kg dw Oral: 0.72 g / kg diet

Source: Supplier data

8.2. EXPOSURE CONTROLS

Appropriate technical controls:

No available data.

Personal protective measures:

Promote the establishment of collective protection measures relative to personal protective measures.

Eye / face protection: Wear approved safety goggles.

Hand protection: Wearing butyl rubber gloves is recommended.

Body protection: Under normal conditions, the required protection is limited to the use of standard work

clothes.

Respiratory protection: If ventilation is insufficient, suitable respiratory protection must be available.

Thermal hazards: Data not available.

Hygiene measures: Observe the usual precautionary measures for chemical use.

Wash hands after use or handling.

Do not inhale aerosols.

It is forbidden to eat, drink or smoke in areas where this material is handled, stored and

used.

Environment protection measures:

Do not discharge into drains or the environment.

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2



SDS No: Print date: Revision date: SDS075 04/03/2014 04/07/2013 Page 7 de 13

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid.

Colour: Data not available.

Odour: Fruity.

Odour Threshold:Data not available.pH:Data not available.Melting / freezing point:Data not available.

Initial boiling point and boiling

range: 82.2°C (1 bar).

Flash point: -4.5°C.

Evaporation rate: Data not available.
Flammability (solid, gas): Data not available.

Upper / lower flammability or

explosive limits: LEL: 2.2%; UEL: 12.5%. Vapour pressure: Data not available.

Vapour density: > 1.

Relative density:Data not available. **Solubility (s):**Data not available.

n-octanol/water partition

coefficient:Data not available.Auto-ignition temperature:Data not available.Decomposition temperature:Data not available.Viscosity:Data not available.Explosive Properties:Data not available.Oxidizing properties:Data not available.

9.2. OTHER INFORMATION

Properties of the propellant gas:

Physical state:Liquefied gas.Colour:Colorless.

Odour: Somewhat ethereal.

PH: Not applicable.

Melting / freezing point: -141°C.

Initial boiling point and boiling

range: -25°C. Flash point: -41°C.

Upper / lower flammability or

explosive limits: LEL: 3%; UEL: 18.6%. Vapour pressure: 810 kPa at 20°C.

Vapour density: 1.89.

Relative density: 0.674 kg/dm³ at 15°C.

Auto-ignition temperature: 350°C.

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2



SDS No: Print date: Revision date: SDS075 04/03/2014 04/07/2013 Page 8 de 13

SECTION 10 STABILITY AND REACTIVITY

10.1. REACTIVITY

Propellant gas may form explosive peroxides in prolonged contact with air or when heated.

10.2. CHEMICAL STABILITY

The product is stable under normal conditions of use.

10.3. Possibility of Hazardous reactions

Ethanol reacts:

- in contact with light metals forming hydrogen
- peroxides
- with halogenated compounds.

10.4. CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods. Avoid heat, flames and other ignition sources.

10.5. INCOMPATIBLE MATERIALS

Relative to propellant gas: oxidizing materials, organic anhydrides, acids, air, strong oxidants.

Relative to the product: oxidizing agents, amines, acids and salts, alkali metals, fluorine, hydrides, peroxides, silver nitrate, mercury nitrate, magnesium perchlorate, hydrogen, phosphorus, arsenic, antimony.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

Information on the mixture:

No data are available on finished product.

Acute Toxicity: Not classified (No available data).

According to data on the components:

Vapours may cause drowsiness and dizziness.

(Supplier data).

Skin corrosion/irritation: Not classified (No available data).

Serious eye damage / eye

irritation: According to data on the components:

The product is classified as "Irritating to eyes". (calculation by the conventional method).

Respiratory or skin sensitization: Not classified (No available data).

Mutagenicity: Not classified (No available data).

Carcinogenicity: Not classified (No available data).

Reproductive Toxicity: Not classified (No available data).

Specific target organ toxicity (STOT) – single exposure:

According to data on the components:

Repeated exposure may cause skin dryness or cracking.

(calculation by the conventional method).

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2

SDS No: Print date: Revision date: SDS075 04/03/2014 04/07/2013 Page 9 de 13

Specific target organ toxicity

(STOT) – repeated exposure: Not classified (No available data).

Aspiration hazard: Not classified (No available data).

Information on likely routes of exposure:

Exposure may occur by dermal and respiratory routes under normal use.

Symptoms related to the physical, chemical and toxicological characteristics:

Refer to section 4.2.

Delayed, immediate and chronic effects of exposure to short or long term:

Refer to section 4.2.

Interactive effects:

No available data.

Absence of specific data:

No available data on similar mixtures.

Information on mixtures and information on substances:

Ethanol:

Irritant to eyes (OECD 405). Skin absorption is considered low. (Supplier data).

Other information:

No additional data available.

SECTION 12 ECOLOGICAL INFORMATION

No data are available on finished product.

12.1. TOXICITY

Acute Toxicity: According to data on the components:

The product is considered as having a low acute toxicity to aquatic organisms.

(Supplier data).

Chronic toxicity: Data not available.

12.2. PERSISTENCE AND DEGRADABILITY

According to data on the components:

The product is considered readily biodegradable.

(Supplier data).

12.3. BIOACCUMULATIVE POTENTIAL

According to data on the components:

The product is considered not potentially bioaccumulative. (Supplier data).

12.4. MOBILITY IN SOIL

No data available.

geprüft am 24.06.2020

SAFETY DATA SHEET

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

Creation date: 18/05/2005 **Version:** 2.2



SDS No: Print date: Revision date: SDS075 04/03/2014 04/07/2013 Page 10 de 13

12.5. RESULTS OF PBT AND VPVB ASSESSMENT

The product has not been evaluated for its properties PBT/vPvB (Regulation EC No. 1907/2006 – Annex XIII).

12.6. OTHER ADVERSE EFFECTS

No additional data available.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. WASTE TREATMENT METHODS

Dispose of according to local regulations.

The mixture must be disposed of appropriately as solvent based chemical products.

Empty packaging should not be treated as household waste: it may contain hazardous residues.

Nomenclature Code (Environmental Code, art. R541-8, Annex II):

14.06: Waste organic solvents, refrigerants and foam / aerosol propellants.

14.06.03*: Other solvents and solvent mixtures.

SECTION 14 TRANSPORT INFORMATION

Accordance with the requirements of ADR / RID / ADNR / IMDG / ICAO / IATA

14.1. **UN** NUMBER

UN 1950.

14.2. UN PROPER SHIPPING NAME

UN 1950, Aerosols, 2.1 (D).

14.3. TRANSPORT HAZARD CLASS(ES)

Hazard Class: 2 Hazard label: 2.1



14.4. PACKING GROUP

Not applicable.

14.5. ENVIRONMENTAL HAZARDS

Not classified.

14.6. SPECIAL PRECAUTIONS FOR USER

Transport by road:

Classification Code (UN):

Orange panels:



(Regulation EC No.1907/2006 amended - Annex II)

LABORATOIRES URGO COMPANY:

BRAND: **URGO**

PRODUCT NAME: **URGO PANSEMENT SPRAY**

Creation date: 18/05/2005

Version: 2.2

SDS No: Print date: Revision date:

04/03/2014 04/07/2013 Page 11 de 13

SDS075

Transport category (ADR): 2 Tunnel restriction code: D Limited quantities (ADR): 120 ml Excepted quantities (ADR): E0

Sea transport:

MFAG No: 126

Air transport:

Classification code (ONU): 1950 Class / division 2.1

Labels: Flammable gas Name of transport Aerosols, Flammable

Other possibliliy

Classification code (ONU): ID8000 Class / division

Miscellaneous Labels:

Name of transport Consummer commodity

Actions in the event of an accident or emergency:

Apply the braking system, stop the engine and isolate the battery by activating the master switch where available.

Inform the appropriate emergency services, giving as much information about the incident or accident and substances involved as possible.

Put on the warning vest and place the self-standing warning signs as appropriate.

Keep the transport documents readily available for responders on arrival.

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind.

14.7. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not applicable.

SECTION 15 REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS / LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

European regulations:

Directive No.93/42/EEC amended: The mixture in the state of finished product is a medical device used in direct physical

contact with the body of the consumer.

It falls within the scope of this Directive concerning medical devices

Regulation EC No.1907/2006

(REACH) amended:

The mixture in the state of finished product is exempt from Title IV "Information in the supply chain".

In contrast, components of the mixture are affected by all the provisions of the Regulation:

- All components subject to registration have been pre-registered.

- No component of the mixture is subject to authorization (Annex XIV) or restriction (Annex

XVII).

- No component is included in the Candidate List for authorization.

Regulation EC No.1272/2008 (CLP)

amended:

The mixture in the state of finished product is excluded from the scope of this regulation on

the classification, packaging and labeling of dangerous substances and mixtures.

- Not subject to hazard classification.

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

 Creation date:
 18/05/2005

 Version:
 2.2



 SDS No:
 SDS075

 Print date:
 04/03/2014

 Revision date:
 04/07/2013

 Page 12 de 13

- Not subject to labeling hazardous properties.

- Not subject to special packaging.

Directive No.75/324/EEC amended: The finished product placed on the market in aerosol form whose volume is less than 50

mL is excluded from the scope of this Directive relating to aerosol dispensers:

- Not subject to the evaluation of flammability.

- Not subject to specific labeling.

Regulation EC No.2004/42

amended: VOC content: No available data.

National regulations (France):

Occupational diseases: Table of occupational diseases: No. 84.

Classification according to French

ICPE regulation: Not applicable.

15.2. CHEMICAL SAFETY ASSESSMENT

The product has not been evaluated.

SECTION 16 OTHER INFORMATION

Procedure used to derive the classification according to Regulation EC No. 1272/2008 (CLP):

Classification	Justification
Flam Aerosol Cat 1; H222 Eye Irrit Cat 2; H319 SOT SE Cat 3; H336 EUH066	Mixture Properties Calculation method Calculation method Data on the components

Full text of hazard categories: F: Highly flammable.

F+: Extremely flammable.

Xi: Irritant.

Flam Liq Cat2: Flammable liquid Category 2. Flam Aerosol Cat1: Flammable aerosol Category 1.

Eye Irrit Cat2: Irritating to eyes Category 2.

STOT SE Cat3: Specific target organ toxicity following a single exposure Category 3.

Press Gas: Gas under pressure.

Flam Gas Cat1: Flammable gas Category 1.

Full text of R phrases: R11: Highly flammable.

R12: Extremely flammable. R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Full text of H phrases: H220: Extremely flammable gas.

H222: Extremely flammable aerosol. H225: Highly flammable liquid and vapour H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.

EUH066: Repeated exposure may cause skin dryness or cracking.

Updated: The SDS has been updated.

Sentences followed by asterisk (*) have been added compared to the previous version.

 Date:
 Subject:
 Version:

 18/05/2005
 Past version
 1.0

 18/12/2012
 Updated
 2.0

geprüft am 24.06.2020

SAFETY DATA SHEET

(Regulation EC No.1907/2006 amended - Annex II)

COMPANY: LABORATOIRES URGO

BRAND: URGO

PRODUCT NAME: URGO PANSEMENT SPRAY

 Creation date:
 18/05/2005

 Version:
 2.2



 SDS No:
 SDS075

 Print date:
 04/03/2014

 Revision date:
 04/07/2013

 Page 13 de 13

 08/02/2013
 Updated
 2.1

 04/07/2013
 Updated
 2.2

 13/02/2014
 Updated
 2.3

This sheet complements the technical sheets but does not replace them. The information contained within is based on our state of knowledge to the product, on the date indicated. These are given in good faith. Moreover the user's attention is drawn to the possible risks incurred when a product is used for purposes other than those for which it was designed. It does in any case exonerate the user from knowing and applying all the regulations governing his activity. He will be solely responsible of the precautions related to the use he makes of the product. All regulatory prescriptions mentioned is to help the user to fulfill his obligations. This list cannot be considered exhaustive. The recipient must ensure that other obligations do not incumbent on him because of texts other than those mentioned.