

according to UK REACH Regulation

## Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 1 of 16

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Plus 6 Silikonspray 400ml

UFI: D8TC-VER6-UWM7-YDAJ

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Lubricant

#### 1.3. Details of the supplier of the safety data sheet

Company name: plus6 Werkzeuge GmbH & Co.KG

Street: Gewerbepark 9
Place: D-06917 Jessen
Telephone: +49(0)3877/95747-6
E-mail: info@plus6.de
Internet: www.plus6.de

1.4. Emergency telephone 111 NHS (National Health Service)

number:

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### **GB CLP Regulation**

Aerosol 1; H222-H229 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

# GB CLP Regulation

## Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics

2-Propanol

Signal word: Danger

Pictograms:





## **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No



# **Safety Data Sheet**

according to UK REACH Regulation

Plus 6 Silikonspray 400ml				
Revision date: 20.03.2024	Product code: 82451A	Page 2 of 16		

	smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P304+P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container according to the official regulations.

# Special labelling of certain mixtures

EUH208 Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

# 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures



according to UK REACH Regulation

# Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 3 of 16

# Relevant ingredients

CAS No	Chemical name	Quantity			
	EC No	Index No	REACH No		
	Classification (GB CLP R	egulation)	•		
106-97-8	butane	25 - < 50 %			
	203-448-7	601-004-00-0	01-2119474691-32		
	Flam. Gas 1, Liquefied ga	as; H220 H280			
75-28-5	isobutane			25 - < 50 %	
	200-857-2	601-004-00-0	01-2119485395-27		
	Flam. Gas 1, Liquefied ga	as; H220 H280			
	Hydrocarbons, C6-C7, n-	alkanes, isoalkanes, cyclics, < 5% r	-hexane	10 - < 20 %	
	921-024-6		01-2119475514-35		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411				
64742-49-0	Hydrocarbons, C7, n-alka	10 - < 20 %			
	927-510-4		01-2119475515-33		
	Flam. Liq. 2, Skin Irrit. 2, H411				
74-98-6	propane	3 - < 5 %			
	200-827-9	601-003-00-5	01-2119486944-21		
	Flam. Gas 1, Liquefied ga				
	Hydrocarbons, C9-C10, r	1 - < 3 %			
	927-241-2		01-2119471843-32		
	Flam. Liq. 3, STOT SE 3,				
67-63-0	2-Propanol			1 - < 3 %	
	200-661-7	603-117-00-0	01-2119457558-25		
	Flam. Liq. 2, Eye Irrit. 2,	STOT SE 3; H225 H319 H336	•		
5989-27-5	(R)-p-mentha-1,8-diene;	d-limonene		< 0.1 %	
	227-813-5	601-096-00-2			
	Flam. Liq. 3, Skin Irrit. 2, Skin Sens. 1B, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 3; H226 H315 H317 H304 H400 H412				

Full text of H and EUH statements: see section 16.



## **Safety Data Sheet**

according to UK REACH Regulation

## Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 4 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
106-97-8	203-448-7	butane	25 - < 50 %
	inhalation: LC	50 = 658 ppm (gases)	
	921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	10 - < 20 %
	inhalation: LC	50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = >	
64742-49-0	927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	10 - < 20 %
	inhalation: LC	50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 =	
	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics	1 - < 3 %
	inhalation: LC: mg/kg	50 = > 4951 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000	
67-63-0	200-661-7	2-Propanol	1 - < 3 %
	inhalation: LC	50 = 47,5 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 5280 mg/kg	
5989-27-5	227-813-5	(R)-p-mentha-1,8-diene; d-limonene	< 0.1 %
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=1	

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

## After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

#### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

# Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high



## **Safety Data Sheet**

according to UK REACH Regulation

## Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 5 of 16

concentrations or in enclosed spaces.

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Danger of bursting container.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

## For non-emergency personnel

First aider: Pay attention to self-protection!

#### For emergency responders

Fight fire with normal precautions from a reasonable distance.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### 6.3. Methods and material for containment and cleaning up

#### For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

#### **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

#### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

## Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

#### Further information on handling

Avoid contact with skin and eyes.



# **Safety Data Sheet**

according to UK REACH Regulation

## Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 6 of 16

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

#### Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

#### Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

## 7.3. Specific end use(s)

No information available.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

# **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5%	n-hexane				
Worker DNEL,	long-term	inhalation	systemic	2035 mg/m³		
Worker DNEL,	long-term	dermal	systemic	773 mg/kg bw/day		
Consumer DN	EL, long-term	inhalation	systemic	608 mg/m³		
Consumer DN	EL, long-term	dermal	systemic	699 mg/kg bw/day		
Consumer DN	EL, long-term	oral	systemic	699 mg/kg bw/day		
64742-49-0	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics					
Worker DNEL,	long-term	inhalation	systemic	2085 mg/m³		
Worker DNEL,	long-term	dermal	systemic	300 mg/kg bw/day		
Consumer DNEL, long-term		inhalation	systemic	447 mg/m³		
Consumer DN	EL, long-term	dermal	systemic	149 mg/kg bw/day		
Consumer DNE	EL, long-term	oral	systemic	149 mg/kg bw/day		

## Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

## 8.2. Exposure controls



# **Safety Data Sheet**

according to UK REACH Regulation

## Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 7 of 16

#### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

EN 166

#### Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

**EN ISO 374** 

#### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

## **Environmental exposure controls**

Observe legal regulations and provisions.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: Lemon

Test method

Boiling point or initial boiling point and -40 °C

boiling range:

Lower explosion limits: 1 vol. % Upper explosion limits: 15 vol. % Flash point: -80 °C

pH-Value (at 20 °C): DIN 19268

Density (at 20 °C): 0,748 g/cm³ DIN 51757

## 9.2. Other information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

# 10.2. Chemical stability

The product is stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.



## **Safety Data Sheet**

according to UK REACH Regulation

## Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 8 of 16

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

#### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

#### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **Further information**

Do not mix with other chemicals.

# **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

## Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to UK REACH Regulation

# Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 9 of 16

CAS No	Chemical name	Chemical name								
	Exposure route	Dose	Species	Source	Method					
106-97-8	butane									
	inhalation (4 h) gas	LC50 658 ppm	Rat	GESTIS						
	Hydrocarbons, C6-C7, n-	-alkanes, isoalkanes, cy	clics, < 5% n-hexane							
	oral	LD50 > 5000 mg/kg	Rat							
	dermal	LD50 > 2800 - 3100 mg/kg	Rat							
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	Rat							
64742-49-0	Hydrocarbons, C7, n-alk	anes, isoalkanes, cyclic	S							
	oral	LD50 5500 mg/kg	Rat							
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de					
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403					
	Hydrocarbons, C9-C10,	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics								
	oral	LD50 > 5000 mg/kg	Rat							
	dermal	LD50 > 5000 mg/kg	Rabbit							
	inhalation (4 h) vapour	LC50 > 4951 mg/l	Rat							
67-63-0	2-Propanol									
	oral	LD50 5280 mg/kg	Rat							
	dermal	LD50 > 2000 mg/kg	Rabbit							
	inhalation (4 h) vapour	LC50 47,5 mg/l	Rat							
5989-27-5	(R)-p-mentha-1,8-diene;	d-limonene			_					
	oral	LD50 > 2000 mg/kg	Rat	Study report (2010)	OECD Guideline 423					
	dermal	LD50 > 2000 mg/kg	Kaninchen	IUCLID						

#### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

## Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.



## **Safety Data Sheet**

according to UK REACH Regulation

## Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 10 of 16

## STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

Based on available data, the classification criteria are not met.

# Information on likely routes of exposure

Ingestion, Inhalation, Skin contact, Eye contact.

Reference to other sections: 2.1, 4.2.

#### Specific effects in experiment on an animal

No information available.

#### 11.2. Information on other hazards

## **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

#### Other information

No information available.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

There are no data available on the mixture itself.



according to UK REACH Regulation

# Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 11 of 16

CAS No	Chemical name	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
06-97-8	butane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has beer develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
5-28-5	isobutane								
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has beer develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Hydrocarbons, C6-C7, n-a	alkanes, isc	alkanes, cyc	lics, < 5%	n-hexane				
	Acute fish toxicity	LC50 mg/l	> 1-10	96 h	Pimephales promelas				
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 1-10	48 h	Daphnia magna				
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)			
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
64742-49-0	Hydrocarbons, C7, n-alka	nes, isoalka	anes, cyclics						
	Acute fish toxicity	LL50 mg/l	> 13,4	96 h	Oncorhynchus mykiss	Study report (2004)	OECD Guideline 203		
	Acute algae toxicity	ErC50	12 mg/l	72 h	Pseudokirchneriella subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	>1 - 10	48 h	Daphnia magna				
	Fish toxicity	NOEC mg/l	1,534	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)			
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
'4-98-6	propane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has beer develo		



Revision date: 20.03.2024

# **Safety Data Sheet**

according to UK REACH Regulation

# Plus 6 Silikonspray 400ml Product code: 82451A Page 12 of 16

	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Hydrocarbons, C9-C10, n	ı-alkanes, is	oalkanes, cyc	lenes, <	2% aromatics		
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna		
67-63-0	2-Propanol						
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna		
5989-27-5	(R)-p-mentha-1,8-diene;	d-limonene					
	Acute fish toxicity	LC50 mg/l	0,72	96 h	Pimephales promelas	Study report (1990)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	0,32	72 h	Pseudokirchneriella subcapitata	Study report (2013)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,307	48 h	Daphnia magna	Study report (2013)	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,37	8 d	Pimephales promelas	Study report (2015)	OECD Guideline 212
	Crustacea toxicity	NOEC mg/l	0,08	21 d	Daphnia magna	Study report (2016)	OECD Guideline 211
	Acute bacteria toxicity	EC50	209 mg/l	3 h	activated sludge of a predominantly domestic sewag	Study report (2010)	OECD Guideline 209

## 12.2. Persistence and degradability

There are no data available on the mixture itself. AOX (mg/l): 0

······································						
CAS No	Chemical name					
	Method Value d Source					
	Evaluation					
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic	s, < 5% n-hexane				
	OECD Guideline 301 F 98% 28					
	Easily biodegradable (concerning to the criteria of the OECD)					

## 12.3. Bioaccumulative potential

There are no data available on the mixture itself.



## **Safety Data Sheet**

according to UK REACH Regulation

## Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 13 of 16

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
75-28-5	isobutane	1,09
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	1,09
67-63-0	2-Propanol	0,05
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene	4,38

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
5989-27-5	(R)-p-mentha-1,8-diene; d-limonene	908,5		Other company data (

## 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

#### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

## List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

# List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

#### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

# **SECTION 14: Transport information**

## Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L



according to UK REACH Regulation

Plus 6 Silikonspray 400ml
Revision date: 20.03.2024 Product code: 82451A Page 14 of 16

Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:no

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU regulatory information**

Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial

ısıııaı

No information available.

emissions:

Directive 2004/42/EC on VOC in

paints and varnishes:

No information available.

#### Additional information



according to UK REACH Regulation

## Plus 6 Silikonspray 400ml

Revision date: 20.03.2024 Product code: 82451A Page 15 of 16

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Aerosol Directive (75/324/EEC)

#### **National regulatory information**

Water hazard class (D): 2 - obviously hazardous to water

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,9.

## Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols Liquefied gas

Flam. Liq: Flammable liquids Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

#### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Aerosol 1; H222-H229	On basis of test data	
Skin Irrit. 2; H315	Bridging principle "Aerosols"	
STOT SE 3; H336	Bridging principle "Aerosols"	
Aquatic Chronic 3; H412	Calculation method	

## Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.



# **Safety Data Sheet**

according to UK REACH Regulation

	Plus	s 6 Silikonspray 400ml		
Revision date: 20.03.2024		Product code: 82451A	Page 16	of 16
11215	Carrage aldin innitation			

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)